



- Remotely controlled
- Adjustable Pan range
- Adjustable Tilt range

## EMC hardened Pan/Tilt unit

The Pan/Tilt unit PT51 is special designed for use in EMC environment in combination with PONTIS EMC cameras. A camera with Pan-Tilt can pan and tilt remotely. Thanks to the Pan/Tilt function, you can see everything at a glance.

### Features:

- Designed for use with camera series Cam5, HDCam6, HDCam7
- Constructed from aluminium profile
- Powder-coated housing, colour RAL 7035 light grey
- Stainless steel screws
- Supplied with accessories for mounting on tripods / wallbrackets

## Technical Data

### ENVIRONMENT

EMC 200 V/m up to 18 GHz

### MECHANICAL

External Dimensions: 100 x 100 x 135 mm (L x W x H)

Maximum load 2 kg

Horizontal plane movement 0 to 350 °

Horizontal speed 6 °/s fixed

Horizontal limit switches adjustable

Vertical plane movement +35 ° to -90 °

Vertical speed 3 °/s fixed

Vertical limit switches internally adjustable

Weight 2.1 kg

### ELECTRICAL

Power supply 24 V, AC

Horizontal motor consumption 1.6 W max.

Vertical motor consumption 2.1 W max.

Prices and specifications are subject to change without notice!

**PONTIS**  
EMC PRODUCTS  
A BRAND OF AUDIOVO

PONTIS EMC Products designed and manufactured by:

Audiovo GmbH  
Irrenloher Damm 30  
92521 Schwarzenfeld  
Germany

Phone +49(9435) 54 19-0  
Fax +49(9435) 54 19-19  
info@audiovo.com  
www.audiovo.com

You can contact directly our local partners for sales and technical support



[www.hvtechnologies.com](http://www.hvtechnologies.com)



[www.toyo.co.jp](http://www.toyo.co.jp)



[zongkui.shao@pontis-emc.com](mailto:zongkui.shao@pontis-emc.com)